

# 650 TREADMILL

With a combination of the latest technology options and the reliability of TRUE's premium warranty, the C650 treadmill provides the performance and efficiency needed for your commercial facility. Patented items like HRC Heart Rate Control® and TRUE's low-impact Soft System® allows your users to have a first-class exercise experience. In addition, a variety of consoles are available to provide multiple levels of features, technology, and asset management.



## FEATURES

- 15.0 MPH (24 KPH) Maximum speed with 15% Maximum incline
- Patented HRC Cruise Control® and Soft System® deck
- Reversible Deck

## SPECIFICATIONS

### DIMENSIONS (L X W X H)

82" x 33" x 60.3" / 208.28 cm x 83.82 cm x 153.16 cm

### SPEED

0.5 to 12 MPH / 0.8 to 19 KPH (0.5 to 15.0 MPH / 0.8 to 24 KPH with Decline)

### INCLINE/DECLINE LEVELS

0% to 15%, (-3% to 15% with Decline)

### PRODUCT WEIGHT

428 lbs /194.1 kg

### COLOR

Charcoal/Black



## CONSOLE OPTIONS



**ENVISION**



**ENVISION  
WITH COMPASS**



**ENVISION 9**



**EMERGE**



**IGNITE**

# PREMIUM 650 SERIES



## C650 TREADMILL

TECHNICAL SPECIFICATIONS	Power Source	120V/20A (NEMA 5-20R receptacle) 230V/15A	
	Cord Length	12' / 3.7 M	
	Drive Motor	5 HP AC Self-Cooling Max Drive	
	Power Factor Correction (PFC)	Standard	
	Incline Motor	1,200 lbs. of Thrust	
	Speed Sensor	Optical	
	Deck	Reversible 1" / 2.54 cm Medium-Density Fiberboard	
	Reversible Deck	Standard	
	Belt	Lubricant Infused Siegling Multi-Ply with PVC Coating	
	Rollers	3" / 8 cm w/ Shielded Bearings	
	Impact System	True Soft System®	
	Frame Construction	Robotically Welded Heavy-Gauge Steel	
	Lubrication	Silax	
	Speed Range	0.5 to 12 MPH / 0.8 to 19 KPH (0.5 to 15.0 MPH / 0.8 to 24 KPH with Decline)	
	Incline/Decline Range	0% to 15%, (-3% to 15% with Decline)	
	Quick Access Control	Speed and Incline on Hand Grips with Start and Stop on Quick Access Point	
	Handrail Design	Extended Handrails with Molded Rubber, Moisture-Resistant Grips	
	Contact Heart Rate Monitoring	Yes	
	Wireless Heart Rate Monitoring	Polar®	
	AVAILABLE CONSOLES	Envision, Envision with Compass, Envision 9 , Emerge, Ignite	
	ASSET TRACKING	EcoFit Compatible	
	SAFETY	Safety Clip	Standard/Non-Removable
		Extended Handrails	Standard
Large Straddle Covers		Standard	
User Detection		User Present Detection™	
REGULATORY APPROVALS	ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC		
EXTRAS	Accessories	Water Bottle Holder, Accessory Tray, Over Molded Reading Rack/Tablet Holder, Power Cord Management, Optional Medical Rails, Optional Decline Feet Kit	
PHYSICAL SPECIFICATIONS	Footprint	82" L x 33" W x 60.3" H / 208.28 cm x 83.82 cm x 153.16 cm	
	Footprint with Decline	82" L x 33" W x 62.5" H / 208.28 cm x 83.82 cm x 158.75 cm	
	Running Surface	60" L x 22" W / 152.4 cm x 55.8 cm	
	Machine Weight	428 lbs / 194.1 kg	
	Shipping Weight	470 lbs / 213.1 kg	
	Maximum User Weight	500 lbs / 226.7 kg	
	Step-Up Height	7" / 17.7 cm (9" / 22.86 cm with Optional Decline)	
Portability	2 Front Transport Wheels		
WARRANTY	Warranty Type	Commercial (all dues paying facilities, regardless of usage)	
	Frame	Lifetime	
	Motor	5 Years	
	Parts	3 Years	
	Labor	3 Years	

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.



truefitness.com | 800.426.6570 | 636.272.7100

©2019 TRUE Fitness Technology, Inc