

200 TREADMILL

The 200 Treadmill provides your commercial facility reliable performance and a high-quality experience with features like HRC Heart Rate Control[®] and TRUE'S low-impact Soft System[®]. The 200 treadmill is the ideal choice for rehabilitation use at health and medical facilities with space-efficiency and low profile design in mind.

FEATURES

- Minimum Speed: 0.5 MPH (0.3 KPH)
- Extended handrails
- HRC Cruise Control®
- TRUE Soft System® deck

SPECIFICATIONS

DIMENSIONS (L X W X H) 83.5" x 32" x 60.5" / 212.09 cm x 81.2 cm x 153.67 cm

SPEED

0.2 to 12.0 MPH / 0.3 to 19 KPH

INCLINE/DECLINE LEVELS

0% to 15%

PRODUCT WEIGHT

349 lbs / 158.3 kg

COLOR

Silver

CONSOLE OPTIONS



TWO WINDOW LCD DISPLAY Standard two window LCD display console featuring 12-15 programs, HRC Heart Rate Control® cruise control, CSAFE power.

TRUE



TWO WINDOW

Standard two window LCD display console featuring 12-15 programs, HRC Heart Rate Control® cruise control, CSAFE power.



200 SERIES



CS200 TREADMILL

| TECHNICAL SPECIFICATIONS - - - - - - - - - - - - - - - - - - - | Power Source | 120/15A (NEMA 5-15 receptacle) dedicated outlet |
|---|--------------------------------|---|
| | Cord Length | 10' / 3.0 M |
| | Drive Motor | 4 HP AC Endura-Drive |
| | Incline Motor | 1,000 lbs. of thrust |
| | Speed Sensor | Optical |
| | Deck | 1" / 2.54 cm Medium Density Fiberboard |
| | Belt | Lubricant Infused Siegling Multi-Ply with PVC Coating |
| | Rollers | 3" / 8 cm w/ Sealed Bearings |
| | Impact System | True Soft System® |
| | Frame Construction | Robotically Welded Heavy-Gauge Steel |
| | Lubrication | Silax |
| | Speed Range | 0.5 to 12.0 MPH / 0.8 to 19.3 KMH |
| | Incline/Decline Range | 0% to 15% |
| | Quick Access Control | Speed, Incline, Start and Stop on Quick Access Point |
| | Handrail Design | Extended Handrails with Molded Rubber, Moisture-Resistant Grips |
| | Contact Heart Rate Monitoring | Yes |
| | Wireless Heart Rate Monitoring | Polar® Compatible |
| CONSOLE . | Display | LCD |
| | Programs | 12 |
| | HRC Workouts | 1 |
| | HRC Cruise Control | Standard |
| | CSAFE Power | Standard |
| | Diagnostic | Standard |
| SAFETY | Safety Clip | Standard |
| | Extended Handrails | Standard |
| | Large Straddle Covers | Standard |
| REGULATORY APPROVALS | | ETL, UL1647, CSA, (CE for 220 v) |
| PHYSICAL SPECIFICATIONS | Footprint | 83.5" L x 32" W x 60.5" H / 212.09 cm x 81.2 cm x 153.67 cm |
| | Running Surface | 60" L x 22" W / 152 <i>4</i> cm x 55.88 cm |
| | Machine Weight | 349 lbs / 158.3 kg |
| | Shipping Weight | 424 lbs / 192.3 kg |
| | Maximum User Weight | 350 lbs / 158.7 kg |
| | Step-Up Height | 6.25" / 15.88 cm |
| | Portability | 2 Front Transport Wheels |
| WARRANTY | Warranty Type | Commercial (non-dues paying facilities with less than 8 hours of usage per day) |
| | Frame | Lifetime |
| | Motor | 5 Years |
| | Parts | 5 Years |
| | Labor | 1 Year |
| | | |

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.