

VAPOR STRYKER SLAT TREADMILL



TRUE heritage and engineering come together to provide your facility with the TRUE Stryker Slat Treadmill. The Stryker features a running surface of vulcanized rubber slats that are more durable and require less maintenance than the conventional conveyor belt system of traditional treadmills. The individual shock-absorbing slats provide a running surface closer to the natural feel of outdoor running for those looking for a more realistic training experience.

FEATURES

- Less downtime and overall lower cost-of-ownership than traditional treadmill
- Requires less maintenance; no need for tracking adjustments, waxing, or flipping of deck with slat system
- Ergonomic pistol-grip handles with thumb controls and center pod with quick speed and incline keys
- Over-molded rubber slat belt with 62 individual slats and running surface of 22"/55 cm x 60"/152 cm
- Three emergency stops for safety (on console, center pod, and safety key)

SPECIFICATIONS

DIMENSIONS (L X W X H)
72" L x 35" W x 64" H /
183 cm x 89 cm x 163 cm

SPEED
.5 to 12.5 MPH / .8 to 20 KPH (0.1 increments)

INCLINE/DECLINE RANGE
0% to 25% (-3% to 22% with Decline Kit)

PRODUCT WEIGHT
599 lbs / 272 kg

COLOR
Matte Black

CONSOLE OPTIONS



**UNITE 22''
TOUCHSCREEN**




**UNITE 16''
TOUCHSCREEN**



**UNITE 10''
TOUCHSCREEN**



**UNITE LED
CONSOLE**



shock-absorbing
slat design



VAPOR STRYKER SLAT TREADMILL

TECHNICAL SPECIFICATIONS

Power Source	110V/20A Dedicated (NEMA 5-20 Receptacle), 220-240V/15A Option Available
Cord Length	12' / 3.7M
Power Factor Correction (PFC)	Standard
Resistance Source	Double-Braking System
Incline Motor	1,200 lbs. of thrust
Speed Sensor	Optical
Slat	62 vulcanized rubber slats - durometer of 75 shore
End Rollers	58 mm diameter with shielded bearings
Slat Belt Support Bearings	22 mm diameter with sealed bearings
Frame Construction	Robotically Welded Heavy-Gauge Steel
Speed Range	.5 to 12.5 MPH / .8 to 20 KPH
Incline/Decline Range	0% to 25% (-3% to 22% with Decline)
Quick Access Control	Mechanical thumb switches and center pod with quick keys (speed and incline) as well as emergency stop
Handrail Design	Continuous MultiGrip Handrails with Molded Rubber, Moisture-Resistant Grips
Contact Heart Rate Monitoring	Yes
User Detection	Person Present Detection
Asset Management	Ecofit

AVAILABLE CONSOLES

UNITE 22", UNITE 16", UNITE 10", and UNITE LED

WORKOUTS

UNITE 22", UNITE 16" and UNITE 10" Consoles	10K, 5K, AIR FORCE, ARMY, CALORIE GOAL, CARDIO CHALLENGE, DISTANCE GOAL, DRAW YOUR OWN, GERKIN, HALF MARATHON, HILL INTERVALS, HRC CRUISE CONTROL, LEG SHAPER, MARINES, MONUMENT WORKOUT, NAVY, PEB, QUICK START, ROLLING HILLS, SINGLE HILL, SPEED INTERVALS, TARGET HRC, TIME GOAL, VIRTUAL RUNS, WEIGHT LOSS HILL
UNITE LED Console	10K, 5K, CALORIE GOAL, CARDIO CHALLENGE, DISTANCE GOAL, GERKIN, HALF MARATHON, HILL INTERVALS, HRC CRUISE CONTROL, LEG SHAPER, QUICK START, ROLLING HILLS, SINGLE HILL, TARGET HRC, TIME GOAL, and WEIGHT LOSS HILL

EXTRAS

Accessories Water Bottle Holders (2), Accessory Tray, Reading Rack/Tablet Holder

PHYSICAL SPECIFICATIONS

Dimensions	72" L x 35" W x 64" H / 183 cm x 89 cm x 163 cm
Running Surface	60" L x 22" W / 56 cm x 152 cm
Machine Weight	599 lbs / 271 kg
Shipping Weight	645 lbs / 293 kg
Shipping Dimensions	80" L x 42" W x 29" H / 203 cm x 107 cm x 74 cm
Maximum User Weight	500 lbs / 227 kg
Deck Step-Up Height	13" / 33 cm

Portability Rear Retractable Transport Wheels

COMMERCIAL WARRANTY

Frame 7 Years (with registration)

Parts 3 Years

Labor 2 Years (with registration)

Consoles 3 Years

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.
To ensure you get the most out of your purchase and receive the full benefits of our warranty, you must register your product within 45 days of purchaser's receipt of this product.



truefitness.com | 800.426.6570 | 636.272.7100

©2026 TRUE Fitness Technology, Inc

REV 1-27-2026